

HUSAR

WINCH

BETTER STRONGER TOUGHER

HUSAR WINCH BST 2000 LBS

BST 2000lbs	Technical specifications
Pull capacity(single line)	2000lbs / 907 kgs
Motor 12V	0.9 hp/0,7kW
Controls	Wired remote control
Gear ratio	153:1
Brake	Automatic
Rope	15m Ø 4mm
Net weight	6,0kg
Fairlead	4-ways rollers fairlead
Dimensions	(L x W x H) 285 x 105 x 106mm



Line speed and motor current (first layer)						
Line pull	Lbs	0	500	1000	1500	2000
	Kgs	0	227	454	680	907
Line speed	M/min	3,2	2,8	2,3	1,8	0,6
Motor current	Amps	12	30	60	90	120

Line pull and cable capacity						
Layer of cable		1	2	3	4	5
Rated line pull per layer	Lbs	2000	1630	1380	1190	1050
	Kgs	906	740	620	540	470
Cable capacity per layer	M	2	4,3	7,2	10,6	15

HUSAR WINCH BST 2500 LBS

BST 2500lbs	Technical specifications
Pull capacity(single line)	2500lbs / 1134 kg
Motor 12V	0,9 KM
Controls	wired/wireless remote control
Gear ratio	153:1
Brake	Automatic
Rope	10m
Fairlead	4-ways rollers fairlead
Net weight	6,5kg
Dimensions	(L x W x H) 300 x 105 x 105mm



Line pull and cable capacity					
Line pull	Lbs	0	1000	2000	2500
	Kg	0	454	907	1132
Line speed	m/min	9,5	6,6	3,6	2,6
Motor current	Amper	12	60	120	140

Line pull and cable capacity						
Layer of cable		1	2	3	4	5
Rated line pull per layer	Lbs	2500	1630	1380	1190	1050
	Kg	1132	740	620	540	470
Cable capacity per layer	m	1,5	3,5	5,9	8,7	10